### Allgemein

IP ermitteln:

```
arp -a
```

login:

```
ssh user@ip
```

Virtual environment

```
  cd sese_project/serious-seeds
  source env/bin/activate
```

Create Database

Start Dev Server

```
    python3 manage.py runserver 0.0.0.0:8000
```

### Turn off power management for network adapter

Create a new systemd service file:

sudo systemctl edit –force –full wifipower.service

Paste the following content into the file:

Code

```
  [Unit]
  Description=Disable WiFi Power Management
  [Service]
  Type=oneshot
  RemainAfterExit=yes
  ExecStart=/sbin/iw dev wlan0 set power_save off
  [Install]
  WantedBy=multi-user.target
```

Save and exit the editor.

Enable the service:

```
  sudo systemctl enable wifipower.service.
```

Start the service immediately:

```
  sudo systemctl start wifipower.service
```

or reboot the Pi for it to take effect:

```
  sudo reboot
```

### Deployment Checklist

- Static Files - Database

### Nginx

```
sudo nano /etc/nginx/sites-available/seriousseeds
```

Next, enable the configuration:

```
sudo ln -s /etc/nginx/sites-available/seriousseeds /etc/nginx/sites-enabled/
```

```
sudo nginx -t
sudo systemctl restart nginx
```

### Gunicorn

### Tutorial

https://www.teachmemicro.com/building-a-django-webserver-on-raspberry-pi-a-step-by-step-guide/

From:
https://wiki.serious-seeds.zwohundertvier.de/ - **Serious Seeds**

Permanent link:
**https://wiki.serious-seeds.zwohundertvier.de/doku.php?id=deployment_raspberry&rev=1760987279**

Last update: **2025/10/20 19:07**